



## ***Approved Floorcoverings for Use with TraxxShield99™***

TraxxShield99™ Rolled Moisture Barrier has been approved for use with a large variety of floorcoverings stated below to suppress moisture vapor emissions in concrete slabs:

Carpet Tile	Broadloom Carpet
Vinyl Composition Tile (VCT)	Engineered Wood (Nail-down or Floating only)
Luxury Vinyl Tile (LVT)	Solid Hardwood (Nail-down only)
Luxury Vinyl Planks (LVP)	Laminates
Solid Vinyl Tile (SVT)	Ceramic/Porcelain
Static Dissipative/Conductive Tile	Natural Stone

In addition, several commercial-quality sheet vinyl floorcoverings have been tested and approved for use with TraxxShield99™. Heat-welded seams are also approved.

Armstrong® Medintone/Medintech™	Mannington® BioSpec™
Armstrong® Connection Corlon™	Mannington® Vivendi™
Shaw® BioLife™	Mannington® Assurance™
Shaw® NatureLife™ Wood	Johnsonite®/Tarkett IQ Optima™
	Johnsonite® Melodia™

**\*Not all Sheet Vinyl products are approved**, so please contact your TRAXX Sales Manager or TRAXX Corporation at 909-623-8032 for approvals on a job-by-job basis.

\* TraxxShield99™ must be adhered to the concrete slab when installing Sheet Vinyl floorcoverings, as the loose-lay option is not approved for sheet products.

\*When installing Sheet Vinyl, it is required to skim-coat the TraxxShield99™ surface with cement-based, latex finish underlayment (Ardex Feather-Finish™, Uzin NC 886, Mapei Planiprep SC™). This step will enhance the surface appearance of your floorcovering.

**\*Linoleum and rubber tile floorcoverings are not approved.**

**Always refer to the TraxxShield99™ website for the latest *Approved Floorcovering Listing*.**

November, 2016