

Carpet Seam Tape

I. PRODUCT IDENTIFICATION

Name: Carpet Seam Tape
Class: Thermoplastic Carpet Seam Tape
Emergency Telephone CHEMTREC:
800-424-9300

II. HMIS (0=minimal hazard; 4= severe)

Health = 0 Flammability = 1 Reactivity = 0

III. HAZARDOUS INGREDIENTS

None per OSHA Regulation:
29CFR1910.1200 None per SARA Title III, Section 313 and
TSCA 40 CRF 372

IV. PHYSICAL DATA

MELTING POINT: 230°F; BOILING POINT: Not established;
ODOR: Neutral; SPECIFIC GRAVITY: 0.98; VAPOR PRESSURE:
Not established; VAPOR DENSITY: Not established

V. FIRE & EXPLOSION HAZARD DATA

FLASH POINT: NA; AUTOIGNITION TEMPERATURE: Not established;
LOWER EXPLOSIVE LIMIT: Not established; UPPER
EXPLOSIVE LIMIT: Not established; EXTINGUISHING MEDIA: A
solid stream of water may scatter molten product. UNUSUAL
FIRE AND EXPLOSION HAZARDS: Material will burn in a fire.
SPECIAL FIRE FIGHTING PROCEDURES: Persons exposed to
products of combustion should wear self-contained breathing
apparatus and full protective equipment. HAZARDOUS COM-
BUSTION PRODUCTS: Carbon dioxide, Carbon monoxide

VI. HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: Inhalation, Ingestion, skin and
eye contact. EFFECTS OF OVEREXPOSURE: Eyes – No irritation
hazard in normal industrial use. Exposure to hot material may
cause thermal burns. Skin – Skin contact at room temperature
is not irritating. Contact with product at elevated temperatures
can result in thermal burns. Inhalation – No irritation hazard in
normal industrial use. Ingestion – Ingestion is not an
anticipated route of exposure.

VII. FIRST AID MEASURES

EYE CONTACT: Use an eye wash to remove a chemical from
your eye regardless of the level of hazard. Flush eye with water
for 15 minutes. Get medical attention. SKIN CONTACT: Wash
affected area(s) thoroughly with soap and water. For hot mate-
rial, immediately immerse in or flush the affected are with large
amounts of cold water to dissipate heat. cover with clean gauze
and do not attempt to remove the material yourself. Seek medi-
cal attention. Medical personnel: coat with mineral oil to soften
material for removal. INHALATION: This material does not
present a hazard if inhaled. Remove to fresh air if necessary.
INGESTION: No hazard in normal industrial use. Do not induce
vomiting. Seek medical attention if symptoms develop.

VIII. SPILL OR LEAK PROCEDURES

SPECIAL PROTECTION: No adverse health effects expected
from the clean-up of spilled material. CLEAN-UP: Allow molten
material to solidify before disposal.

IX. PROTECTIVE EQUIPMENT

No safety equipment required other than goggles.

X. SPECIAL PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN

STIXX believes that data set forth herein is accurate as of the
date hereof, and makes no warranty with respect thereto and
expressly disclaims all liability for reliance thereon. Such data
are offered solely for your consideration, investigation and
verification.