

SAFETY DATA SHEET

PRODUCT: Carpet Edge Sealer

1. Product and Company Identification

IDENTITY	FAST FUSION CARPET EDGE SEALER	MANUFACTURERS	
SYNONYMS	Carpet Edge Sealer	NAME	TRAXX CORPORATION
CAS NUMBER	NONE	ADDRESS	1201 E. LEXINGTON AVE. POMONA, CA 91766
DATE OF LAST ALTERATION	June 1, 2015	EMERGENCY	
		TELEPHONE NO.	(909) 623-8032
		INFORMATION	
		TELEPHONE NO.	(909) 623-8032

2. Hazards Identifications

HMIS Rating:				
Health: 1	Fire: 0	Reactivity: 0	PPE: B	
This material is formulated with trade secret ingredients and does not contain any hazardous substances at or above OSHA and WHMIS reportable levels. Use this product as intended				

3. Composition/Information on Ingredients

HAZARDOUS INGREDIENTS			
HAZARDOUS COMPONENTS	C.A.S.Number	TLV/PEL	Weight Percent
Vinyl acetate (residual)	108-05-4	10 ppm	Less than 0.2%

4. First-Aid Measures

EMERGENCY AND FIRST AID PROCEDURES:
Get medical attention if irritation or other symptoms occur.
1. INHALATION: REMOVE FROM AREA TO FRESH AIR. SEEK MEDICAL ADVICE. (PRIMARY ROUTE OF EXPOSURE IS INHALATION).
2. EYES: MAY CAUSE EYE IRRITATION, FLUSH WITH WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.
3. SKIN: MAY CAUSE SKIN IRRITATION, SEEK MEDICAL ADVICE.
4. INGESTION: NOT APPLICABLE UNDER NORMAL USE.

5. Fire-Fighting Measures

FIRE AND EXPLOSION HAZARD DATA			
APPEARANCE AND ODOR	White opaque viscous liquid with slight vinyl acetate odor.		
BOILING POINT ((760 mm, Hg)	100°C (212°F)	MELTING POINT	N/A
pH	5 - 7		
SPECIFIC GRAVITY (H ₂ O=1)	1.05	VAPOR PRESSURE AT 20°C	N/A
VAPOR DENSITY (AIR=1)	N/A	WATER SOLUBILITY/MISCIBILITY.	Moderately soluble
PERCENT NON-VOLATILES	56%	EVAPORATION RATE	N/A
FLASH POINT	N/A	(BUTYL ACETATE = 1)	
EXTINGUISHING			
MEDIA:	WATER, SAND, CO ₂ AND CHEMICAL EXTINGUISHERS.		
SPECIAL FIRE FIGHTING PROCEDURES:	USE NORMAL FIREFIGHTING METHODS FOR FIRES.		
UNUSUAL FIRE AND EXPLOSION HAZARDS:	NONE		

6. Accidental Release Measures

SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

SPILLED SUSTANCE INCREASES RISK OF SLIPPING..

WASTE DISPOSAL METHOD:

IF DISPOSED OR DISCARDED IN ITS PURCHASED FORM, INCINERATION IS PREFERABLE. DRY LAND DISPOSAL IS ACCEPTABLE IN MOST STATES. IT IS, HOWEVER, THE USER'S RESPONSIBILITY TO DETERMINE AT THE TIME OF DISPOSAL WHETHER THIS PRODUCT MEETS FEDERAL, STATE OR LOCAL REGULATIONS.

7. Handling and Storage

PRECAUTIONS FOR SAFE HANDLING AND USE

STORE IN COOL PLACE. KEEP FROM FREEZING. KEEP AWAY FROM OPEN FLAME AND CHILDREN. KEEP CONTAINER CLOSED. AVOID REPEATED OR PROLONGED CONTACT WITH SKIN. FOR INDUSTRIAL USE ONLY.

8. Exposure Controls and Personal Protection

CONTROL MEASURES

RESPIRATORY PROTECTION: GENERALLY NOT REQUIRED.

VENTILATION: NORMAL ROOM VENTILATION WITH FANS IF NECESSARY.

PROTECTIVE GLOVES: GENERALLY NOT REQUIRED.

EYE PROTECTION: SAFETY GLASSES RECOMMENDED.

WORK/HYGIENE PRACTICES: GENERAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE APPLICABLE.

9. Physical and Chemical Properties

APPEARANCE AND ODOR White opaque viscous liquid with slight vinyl acetate odor.

BOILING POINT ((760 mm, Hg)	100°C (212°F)	MELTING POINT	N/A
pH	5 - 7		
SPECIFIC GRAVITY (H ₂ O=1)	1.05	VAPOR PRESSURE AT 20°C	N/A
VAPOR DENSITY (AIR=1)	N/A	WATER SOLUBILITY/MISCIBILITY.	Moderately soluble
PERCENT NON-VOLATILES	56%	EVAPORATION RATE	N/A
FLASH POINT	N/A	(BUTYL ACETATE = 1)	

10. Stability and Reactivity

REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID: AVOID CONTACT WITH OXIDIZING AGENTS.

INCOMPATIBILITY

(MATERIALS TO AVOID) OXIDIZING AGENTS

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE & CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

11. Toxicological Information**HEALTH HAZARD DATA**

EFFECTS OF OVEREXPOSURE:

ACUTE OVEREXPOSURE:

BASED ON THE AVAILABLE DATA TOXIC EFFECTS ARE NOT EXPECTED AFTER SINGLE ORAL EXPOSURE.

PRODUST DETAILS:

ROUTE OF EXPOSURE	RESULT/EFFECT	SPECIES/TEST SYSTEM
ORAL	LD 50: 2000 MG/KG	RAT

EYE IRRITATION:

VAPORS MAY CAUSE EYE IRRITATION.

SKIN IRRITATION:

PROLONGED SKIN CONTACT MAY CAUSE SKIN IRRITATION.

INGESTION:

WILL CAUSE IRRITATION OF THE DIGESTIVE TRACT IF INGESTED.

CHRONIC OVEREXPOSURE:

NO TOXICOLOGICAL TEST DATA IS AVAILABLE FOR THE WHOLE PRODUCT.

12. Ecological Information**Toxicity**

No expected damaging effects to aquatic organisms. According to current knowledge adverse effects on water purification plants are not expected.

Degradability

Not readily biodegradable.

Other adverse effects

None Know

13. Disposal Considerations**Product Disposal**

Dispose of according to regulations by incineration in a special waste incinerator. Small quantities may be disposed of by incineration in an approved facility. Observe local/state/federal regulations.

Packaging Disposal

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations.

Recommended cleaning agent: water

14. Transport Information**US DOT & TDG SURFACE**

Valuation..... Not regulated for transport

Other Information.....Protect from freezing, when exposed to cold temperatures approaching 0°C (32°F) or below.

15. Regulatory Information**U.S. Federal Regulations**

TSCA inventory status:

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical Substance Inventory.

This material does not contain any TSCA 12 (b), CERCLA, SARA, and SARA 313 regulated chemicals above minimum levels.

16. Other Information**DISCLAIMER:**

This Safety Data Sheet meets the requirements of the Federal OSHA Hazard Communication Standard (28 CFR1910.1200).

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. TRAXX Corporation MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the TRAXX product is fit for a particular purpose and suitable for user's method of use or application.