

SAFETY DATA SHEET (SDS)

PRODUCT: KOOL GLIDE CARPET SEAMING TAPE

1. Product and Company Identification

PRODUCT NAME: KOOL GLIDE HOT MELT CARPET SEAMING TAPE	MANUFACTURERS NAME: TRAXX CORPORATION
SYNONYMS: Heat Bond Seaming Tape	ADDRESS: 1201 E. LEXINGTON AVE. POMONA, CA 91766
CAS NUMBER: None	EMERGENCY TELEPHONE NO: 888-872-9926
DATE PREPARED: June 1, 2015	INFORMATION TELEPHONE NO: (909) 623-8032
PREPARED BY: C.K.PATEL	

2. Hazard Identification

HMIS Rating:	Health: 0	Fire: 0	Reactivity: 0	PPE: B
This material is formulated with trade secret ingredients and does not contain any hazardous substances at or above OSHA and WHMIS reportable levels. Use this product as intended				

3. Composition/Information on Ingredients

HAZARDOUS INGREDIENTS
None per OSHA Regulations: 29CFR1910.1200
None per SARA Title III, Section 313 and TCA 40 CRF 372
Hazardous Components: None
Non Hazardous Components: Resin, Polymers, Inert Ingredients

4. First-Aid Measures

EMERGENCY AND FIRST AID PROCEDURES:	
INHALATION:	If exposed to fumes from overheating/charring or combustion of adhesive, remove to fresh air.
EYES:	Flush with large amount of cool water. Contact physician if irritation persists.
SKIN:	If burned by contact with molten adhesive, cool as quickly as possible with water. Do not attempt to remove adhesive from skin. Burns should be treated as thermal burns. Obtain medical attention for burns.
INGESTION:	Material is not likely to be ingested. Consult a physician if ingested.

5. Fire-Fighting Measures

FIRE AND EXPLOSION HAZARD DATA			
FLASH POINT	N/A	AUTOIGNITION TEMPERATURE	N/A
FLAMMABLE LIMITS IN AIR, % BY VOLUME	N/A	LOWER (LEL)	UPPER (UEL)
EXTINGUISHING MEDIA	Foam, Dry Chemical, CO ₂	N/A	N/A
SPECIAL FIRE FIGHTING PROCEDURES	None		
UNUSUAL FIRE AND EXPLOSION HAZARDS	None		

6. Accidental Release Measures

SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Not applicable for product in purchase form.

WASTE DISPOSAL METHOD: Dispose according to Federal, State and Local regulations.

7. Handling and Storage

PRECAUTIONS FOR SAFE HANDLING AND USE

PRECAUTION FOR HANDLING AND STORING: Keep out of reach of children. Avoid excessive heat and freezing.

OTHER PRECAUTIONS: Prevent or mitigate the generation of irritating vapors from overheating/charring of adhesive by insuring the iron is clean and operating at proper temperatures.

8. Exposure Controls and Personal Protection

CONTROL MEASURES

RESPIRATORY PROTECTION: Not required.

VENTILATION: Normal room ventilation with fans if necessary.

PROTECTIVE GLOVES: Not required.

EYE PROTECTION: Safety glasses recommended.

WORK/HYGIENE PRACTICES: General hygiene and safe handling procedures are believed to be generally applicable.

9. Physical and Chemical Properties

PHYSICAL DATA

APPEARANCE AND ODOR: Odorless, milky white/amber color solid adhesive covering a woven fabric scrim and paper.

BOILING POINT ((760 mm, Hg)	N/A	SPECIFIC GRAVITY (H ₂ O=1)	0.98
-----------------------------	-----	---------------------------------------	------

VAPOR PRESSURE AT 20°C	N/A	VAPOR DENSITY (AIR=1)	N/A
------------------------	-----	-----------------------	-----

SOLUBILITY IN WATER:	Insoluble	PERCENT VOLATILES (BY VOLUME)	0
----------------------	-----------	-------------------------------	---

EVAPORATION RATE (BUTYL ACETATE = 1)	N/A	pH	N/A
--------------------------------------	-----	----	-----

VOLATILE ORGANIC COMPOUNDS (VOC) Zero

VOLATILE ORGANIC EMISSIONS (VOE) None @ ambient temperature

VOLATILE ORGANIC EMISSIONS (VOE) Negligible @ application temperature
<0.08 mg/m³ (Cal/OSHA PEL 37 mg/m³)

10. Stability and Reactivity

REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: Excessive Heat

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion Products

INCOMPATIBILITY:
(MATERIALS TO AVOID) Strong Oxidizing Agents

HAZARDOUS POLYMERIZATION: Will Not Occur

11. Toxicological Information

HEALTH HAZARD DATA

PRIMARY ROUTE OF ENTRY: N/A

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Overheating/charring may generate irritating vapors.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Molten adhesive will cause skin burns.

EFFECT OF OVEREXPOSURE: None Known

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None Known

HEALTH HAZARDS (Acute and Chronic): None

CARCINOGENICITY: This product contains No Carcinogens as listed by NTP, IRAC and OSHA

12. Ecological Information

Toxicity

None Known

Degradability

Not readily biodegradable.

Other adverse effects

None Know

13. Disposal Consideration

Product & Packaging Disposal

Dispose of according with the local/regional/state/federal/international regulations.

14. Transport Information

Not regulated per U.S.DOT, IATA or IMO

15. Regulatory Information

U.S. Federal Regulation and State Regulations

Fire Hazard – No Pressure Hazard – No Reactivity Hazard – No

16. Other Information

DISCLAIMER:

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (28 CFR1910.1200). The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. TRAXX Corporation MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the TRAXX product is fit for a particular purpose and suitable for user's method of use or application.