



Approved Floorcoverings for Use with TraxxShield100™

December, 2018

TraxxShield100 Rolled Moisture Barrier has been approved for use with a large variety of floorcoverings stated below to suppress moisture vapor emissions in concrete slabs:

Approved Floor Coverings

VCT	Carpet Tile
LVT	Porcelain Tile/Natural Stone
LVP	Engineered Wood-Floating
Electrostatic SVT	Ceramic Tile

Contact Traxx Technical Services at 909-623-8032 regarding:

Sheet Vinyl/Rubber Flooring/Sports Flooring/Wood Courts

Broadloom Carpet

***Linoleum and rubber tile floorcoverings are not approved.**

In addition, several commercial-quality sheet vinyl floorcoverings have been tested and already approved for use with TraxxShield100. Heat-welded seams are also approved.

Armstrong® Medintone/Medintech™	Mannington® BioSpec™ Homogeneous
Armstrong® Connection Corlon™	Mannington® Vivendi™
Shaw® BioLife™	Mannington® Assurance™
Shaw® NatureLife™ Wood	Mannington Realities/Relay RE
Teknoflor Forestscapes	Johnsonite®/Tarkett IQ Optima™
Takiron	Johnsonite® Melodia™
Lonseal Lonwood	Shannon Specialty

* TraxxShield100 must be adhered to the concrete slab when installing Sheet Vinyl floorcoverings, as the loose-lay option is not approved for sheet products.

*When installing Sheet Vinyl, it is required to skim-coat the TraxxShield100 surface with cement-based, latex finish underlayment (Ardex Feather Finish, Uzin NC 888, Mapei Planiprep SC). This step will enhance the surface appearance of your floorcovering.

Always refer to the TraxxShield100 website for the latest *Approved Floorcovering Listing*.