

TRAXXSHIELD 100

ROLLED MOISTURE BARRIER™

Approved Floorcoverings for Use with TraxxShield100™

TraxxShield100 Rolled Moisture Barrier has been approved for use with a large variety of floorcoverings stated below to suppress moisture vapor emissions in concrete slabs:

Approved Floor Coverings

Vinyl Composition Tile (VCT)*	Engineered Wood (Nail-Down or Floating)
Luxury Vinyl Tile (LVT)*	Solid Wood (Nail-Down Only)
Luxury Vinyl Planks (LVP)*	Laminates
Solid Vinyl Tile (SVT)*	Ceramic Tile/Porcelain/Natural Stone
Static Dissipative Conductive Tile*	

Contact Traxx Technical Services at 909-623-8032 regarding:

Sheet Vinyl**	Wood Courts
Rubber Flooring	Broadloom Carpet
Sports Flooring	*Linoleum and rubber tile floorcoverings are not approved

In addition, several commercial-quality sheet vinyl** floorcoverings have been tested and already approved for use with TraxxShield100. Heat-welded seams are also approved.

Armstrong® Medintone/Medintech™	Mannington® BioSpec™ Homogeneous
Armstrong® Connection Corlon™	Mannington® Vivendi™
Shaw® BioLife™	Mannington® Assurance™
Shaw® NatureLife™ Wood	Mannington Realities/Relay RE
Teknoflor Forestscapes	Johnsonite®/Tarkett IQ Optima™
Takiron	Johnsonite® Melodia™
Lonseal Lonwood	Shannon Specialty

***When installing resilient flooring (Sheet Vinyl, VCT, LVT, LVP, SVT, ElectroStatic Tile):** It is required to skim-coat the top surface of TraxxShield100™ with a Portland cement-based, latex finishing underlayment (like Ardex Feather Finish®, UZIN NC 888, or Mapei Planiprep™ SC)

**** TraxxShield100 must be adhered to the concrete slab when installing Sheet Vinyl floorcoverings, as the loose-lay option is not approved for sheet products.**

Always refer to the TraxxShield100 website for the latest *Approved Floorcovering Listing*.