SAFETY DATA SHEET

PRODUCT: CARPETSHIMS

1. Product and Company Identification

PAGE 1 OF 3

IDENTITY CARPETSHIMS - COMPOSITE RAMP MANUFACTURERS

NAME TRAXX CORPORATION

SYNONYMS PARTICLEBOARD RAMP ADDRESS 1201 E. LEXINGTON AVE.

POMONA, CA 91766

CAS NUMBER NONE EMERGENCY

TELEPHONE NO. (909) 623-8032

DATE OF LAST ALTERATION June 1, 2015 INFORMATION

TELEPHONE NO. (909) 623-8032

2. Hazards Identifications

HMIS Rating:

Health: 0 Fire: 1 Reactivity: 0 PPE: B

This material does not contain any hazardous substances at or above OSHA, CARB and WHMIS reportable levels.

No added formaldehyde adhesive and is exempted by CARB formaldehyde emission standards under section 93120.2(a)

3. Composition/Information on Ingredients

 MAIN COMPONENTS
 CAS#
 PERCENTAGE

 HARDWOOD/SOFTWOOD
 NONE
 97.0% - 98.0%

 pMDI
 9016-87-9
 2.0% - 3.0 %

pMDI: The polymeric diphenylmethane diisocyanate binder used is generally reacted into polyuria and biurets, a small number of urethane and polyurete bonds may also be formed. This product does not liberate MDI vapor. MDI and pMDI are not classified as carcinogenic by ACGIH or IARC, they are not regulated as carcinogens by OSHA nor listed as carcinogens by NTP.

4. First-Aid Measures

EMERGENCY AND FIRST AID PROCEDURES

- 1. INHALATION: REMOVE FROM AREA TO FRESH AIR. IF PERSISTENT IRRITATION, SEVERE COUGHING, BREATHING DIFFICULTIES OR RASH OCCUR. SEEK MEDICAL ADVICE. (PRIMARY ROUTE OF EXPOSURE IS INHALATION).
- 2. EYES: SAW DUST MAY MECHANICALLY IRRITATE THE EYE RESULTING IN REDNESS OR WATERING. FLUSH WITH WATER FOR AT LEAST 15 MINUTES TO REMOVE DUST PARTICLES. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.
- 3. SKIN: VARIOUS SPECIES OF WOOD DUST CAN ELICIT ALLERGIC CONTACT DERMATITIS IN SENSITIZED INDIVIDUALS AFTER REPETITIVE CONTACT. IF A RASH, OR PERSISTENT IRRITATION, OR DERMATITIS OCCURS, SEEK MEDICAL ADVICE.
- 4. INGESTION: NOT APPLICABLE UNDER NORMAL USE.

Fire-Fighting Measures

FIRE AND EXPLOSION HAZARD DATA

FLASH POINT AUTOIGNITION TEMPERATURE 400-500°F

(TEST METHOD) N/A

FLAMMABLE LIMITS IN AIR, PERCENT BY VOLUME LOWER UPPER

WOOD DUST (LEL) APPROX. 40g/M² (UEL) N/A

EXTINGUISHING

MEDIA: WATER, SAND, CO, AND CHEMICAL EXTINGUISHERS.

SPECIAL FIRE FIGHTING

PROCEDURES: USE NORMAL FIREFIGHTING METHODS FOR WOOD FIRES.

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

MATERIAL NAME: CARPETSHIMS PAGE 2 OF 3

6. Accidental Release Measures

SPILL OR LEAK PROCEDURES

NOT APPLICABLE FOR PRODUCT IN PURCHASED FORM. SAW DUST AND SCRAPS MAY BE VACUUMED OR SHOVELED FOR RECOVERY OR DISPOSAL. AVOID DUSTING CONDITIONS; PROVIDE GOOD VENTILATION WHERE DUSTING IS POSSIBLE. USE NIOSH/OSHA APPROVED DUST RESPIRATOR AND GOGGLES WHERE VENTILATION IS NOT POSSIBLE.

7. Handling and Storage

PRECAUTIONS FOR SAFE HANDLING AND USE

SPECIAL HANDLING PRECAUTIONS ARE REQUIRED. PARTICLEBOARD PANELS ARE COMBUSTIBLE. KEEP IN COOL, DRY PLACE AWAY FROM OPEN FLAME AND OTHER SOURCES OF IGNITION. WEAR GLOVES TO AVOID SPLINTERS AND SKIN PUNCTURE.

8. Exposure Controls and Personal Protection

CONTROL MEASURES

PRECAUTIONS:

IF THIS PRODUCT IS USED IN A PROCESS WHICH GENERATES DUST LEVELS IN EXCESS OF THE ALLOWABLE EXPOSURE LIMIT(S) FOR WOOD DUST, A NIOSH/SHA APPROVED DUST RESPIRATOR AND GOGGLES SHOULD BE WORN. DUE TO THE EXPLOSIVE POTENTIAL OF WOOD DUST WHEN SUSPENDED IN AIR, PRECAUTIONS SHOULD BE TAKEN TO PREVENT SPARKS OR OTHER IGNITION SOURCES IN VENTILATION SYSTEMS. USE OF TOTALLY ENCLOSED MOTORS IS RECOMMENDED OR MAY BE WARRANTED IF PROCESS GENERATES EXCESSIVE LEVELS OF WOOD DUST.

9. Physical and Chemical Properties

PHYSICAL DATA

BOILING POINT ((760 mm, Hg)	N/A	MELTING POINT	N/A
рН	N/A		
SPECIFIC GRAVITY (H ₂ O=1)	0.8	VAPOR PRESSURE AT 20°C	N/A
VAPOR DENSITY (AIR=1)	N/A	SOLUBILITY IN WATER % BY WT.	Not soluble
PERCENT VOLATILES		EVAPORATION RATE	N/A
BY VOLUME	0	(BUTYL ACETATE = 1)	
APPEARANCE AND ODOR BROWN	OR TAN, SLIGHTLY AROMATIC W	OOD ODOR.	

10. Stability and Reactivity

REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID: AVOID CONTACT WITH OXIDIZING AGENTS. AVOID OPEN FLAME. PRODUCT MAY IGNITE AT TEMPERATURE IN EXCESS OF 400°F (204°C).

INCOMPATIBILITY

(MATERIALS TO AVOID) OXIDIZING AGENTS AND DRYING OILS.

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE, ALIPHATIC ALDEHYDES, ROSIN ACIDS, TERPENES,

AND POLYCYCLIC AROMATIC HYDROCARBONS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

MATERIAL NAME: CARPETSHIMS PAGE 3 OF 3

11. Toxicological Information

HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

ACUTE OVEREXPOSURE:

WOOD SAW DUST CAN IRRITATE THE EYES AND BREATHING PASSAGES. SOME WOOD SPECIES MAY CAUSE SKIN AND RESPIRATORY IRRITATION. CHEMICAL EFFECTS FROM SOME WOOD SPECIES CAN RESULTS IN RESPIRATORY ALLERGIES. RESPIRATORY AILMENTS HAVE INCLUDED BROCHITIS, IMPAIRMENT OF BREATHING FUNCTIONS, AND ASTHMA. EXCESSIVE CONCENTRATION MAY CAUSE DEPOSITS IN NASAL.

CHRONIC OVEREXPOSURE:

SOME SPECIES OF WOOD DUST CAN ELICIT ALLERGIC CONTACT DERMATITIS IN SENSITIZED INDIVIDUALS AS WELL AS MECHANICAL IRRITATION RESULTING IN ERYTHEMA AND HIVES. PROLONGED EXPOSURE TO CERTAIN SPECIES OF HARDWOOD DUST HAVE BEEN STATISTICALLY ASSOCIATED WITH NASAL CANCER. FORMALDEHYDE HAS BEEN SHOWN TO CAUSE CANCER IN CERTAIN LABORATORY ANIMALS AT EXTREME CONDITIONS. FORMALDEHYDE MAY BE IRRITATING TO THE EYES, NOSE, SKIN, AND MAY AGGRAVATE EXISTING RESPIRATORY PROBLEMS AND CAUSE ALLERGIES TO SUSCEPTIBLE PERSONS.

12. Ecological Information

Toxicity

Not expected

Degradability

Will eventually decompose.

Other adverse effect

Not Known

13. Disposal Considerations

Product and Packaging Disposal

Dispose of according to local/state/federal regulations.

14. Transport Information

US DOT & TDG SURFACE

Valuation...... Not required for transport

Other Information.... None

15. Regulatory Information

This Material does not contain any TSCA 12(b), CERLA, SARA, and SARA 313 regulated chemicals above minimum levels.

16. Other Information

DISCLAIMER:

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (28 CFR1910.1200).

TRAXX CORPORATION BELIEVES THE INFORMATION CONTAINED IN THIS SDS TO BE ACCURATE AT THE TIME OF PREPERATION AND HAS BEEN COMPILED USING SOURCES BELIEVED TO BE RELIABLE. THE INFORMATION SET FORTH HEREIN IS OFFERED AS A SERVICE TO OUR CUSTOMERS AND IS NOT INTENDED TO RELIEVE A CUSTOMER FROM ITS RESPONSIBILITY TO DETERMINE THE SUITABILITY OF THIS INFORMATION OR OF THE MATERIALS DESCRIBED HEREIN FOR PURCHASER'S PURPOSES, TO INVESTIGATE OTHER SOURCES OF INFORMATION, TO COMPLY WITH ALL LAWS AND PROCEDURES REGARDING SAFE USE OF THESE MATERIALS; AND TO USE THESE MATERIALS IN A SAFE MANNER. ALTHOUGH THIS INFORMATION IS BELIEVED TO BE ACCURATE, TRAXX SPECIFICALLY DISCLAIMS RESPONSIBILITY FOR ANY INACCURACY SET FORTH HEREIN. THUS, TRAXX DISCLAIMS LIABILITY OF ANY KIND ARISING FROM ANY PARTY'S USE OF OR RELIANCE ON INFORMATION OF RECOMMENDATIONS SET FORTH HEREIN. FURTHERMORE, NO WARRANTY OF ANY KIND SHALL BE CONSTRUED TO ARISE BY IMPLICATION FROM ANY INFORMATION OR RECOMMENDATION CONTAINED HEREIN, OR OTHERWISE.

06012015