

KOVARA[®] / VAPORSHIELD[™]

Box Grid Application Method

KOVARA[®] / VAPORSHIELD[™] application for light to heavy traffic and rolling loads

Overview

The Box Grid Application Method is used when there is a need to affix KOVARA[®] / VAPORSHIELD[™] MBX or 95 to the concrete slab:

- A 5-foot x 5-foot box grid is recommended in locations with light rolling loads or light foot traffic. This includes but is not limited to low frequency hospital bed, medical equipment, pallet jack, or office chair traffic.
- A 2.5-foot x 2.5-foot box grid is recommended in locations with moderate to heavy rolling loads or moderate to heavy foot traffic. This includes but is not limited to moderate or high frequency hospital bed, medical equipment, pallet jack, or office chair traffic. A 2.5-foot x 2.5-foot box grid is also recommended at flooring thresholds with any expected rolling loads and on ramped flooring.

Materials

KOVARA[®] / VAPORSHIELD[™] MBX and 95 are affixed to the concrete slab using KOVARA[®] / VAPORSHIELD[™] Double-Sided Tape:

- For a 5-foot x 5-foot box grid, 3 rolls of KOVARA[®] / VAPORSHIELD[™] Double-Sided Tape are required per roll of KOVARA[®] / VAPORSHIELD[™] MBX or 95
- For a 2.5-foot x 2.5-foot box grid, 6 rolls of KOVARA[®] / VAPORSHIELD[™] Double-Sided Tape are required per roll of KOVARA[®] / VAPORSHIELD[™] MBX or 95

Installation

Determine the required layout of the KOVARA[®] / VAPORSHIELD[™] Double-Sided Tape to form the box grid. Using a chalk line or straight edge, mark the floor where the KOVARA[®] / VAPORSHIELD[™] Double-Sided Tape box grid will be positioned.

Begin placing the tape by anchoring it centered across one chalk line and pull the tape across the entire length of the line. Set the KOVARA[®] / VAPORSHIELD[™] Double-Sided Tape in place and roll the tape, ensuring that you have removed any wrinkles and the tape is flat. Continue to install KOVARA[®] / VAPORSHIELD[™] Double-Sided Tape centered over each box grid line marked on the floor. Roll all tape lines with either a hand roller or a 75–100-pound resilient roller.

DO NOT OVERLAP KOVARA[®] / VAPORSHIELD[™] DOUBLE-SIDED TAPE. DO NOT REMOVE THE TOP RELEASE FILM FROM THE DOUBLE-SIDED TAPE AT THIS TIME.

Upon completion of the box grid, refer to the installation instructions on the KOVARA[®] / VAPORSHIELD[™] MBX or 95 product pages on traxxcorp.com. When the MBX or 95 product is positioned over the grid, sequentially remove the top release paper of the Double-Sided Tape to affix the MBX or 95 to the concrete. Roll all membrane with a 75–100-pound resilient roller before continuing with the finished flooring installation.

Contact TRAXX Technical Services for any questions regarding the required usage and installation process for the KOVARA[®] / VAPORSHIELD[™] Box Grid Application Method.

Traxxcorp.com | Customer Service: 1-909-623-8032

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate and is offered for consideration, investigation, and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third-party right.

KOVARA®, KOVARA® / VAPORSHIELD™ are trademarks of TRAXX Corporation. This trademark list has been compiled using the available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2023 TRAXX Corporation. All rights reserved.

HEADQUARTERS: 1201 E. Lexington Avenue - Pomona, CA 91766 | USA.

JUNE 2023

