

KOVARA® / VAPORSHIELD™ AB 300

floor moisture barrier

Fast protection for flooring assemblies, now with peel and stick application

The trusted KOVARA® / VAPORSHIELD™ moisture barrier with advanced adhesive formulation

The KOVARA® / VAPORSHIELD™ AB 300 floor moisture barrier is a patent-pending, self-adhered moisture barrier designed to be installed directly to concrete floor slabs and before floor covering application. It is specially designed to help protect floor adhesives and finished flooring from staining, warping and does not promote mold growth resulting from moisture vapor and alkaline salt infiltration through the concrete slab. Its self-adhesive technology allows fast, secure installation on slabs with up to 100% relative humidity.

KOVARA® / **VAPORSHIELD™** AB 300 product benefits:

- Reduces installation time from days to hours
- Split release liner for quick peel-and-stick application – no box grid of tape needed
- Supports heavy floor traffic and rolling loads
- · No primer needed

- Mineral top coat readily accepts most adhesives
- Less downtime and business disruption
- No shifting or buckling from heavy traffic and rolling loads
- No shot blasting required; self-leveling only needed for uneven floors

KOVARA® / VAPORSHIELD™ is now a TRAXX moisture mitigation product.



Faster Installation

The AB 300 floor moisture barrier features best-in-class adhesion to the substrate. This KOVARA®

/ VAPORSHIELD™ product represents a moisture
mitigation solution that can be applied faster, simpler and
cleaner than epoxies and other liquid moisture barriers.



KOVARA® / VAPORSHIELD™ AB 300 QUICK SPECS:

Thickness: 41 mils (not including 2 mil release liner)

Roll Size: 5' x 100' (500 sq. ft.)

Roll Weight: 90 lb. Shelf Life: 1 year

Pallet Quantity: 12 rolls

TRAXX's Technical Services team can work with you to review the existing conditions and ensure a smooth installation.

KOVARA® / VAPORSHIELD™ AB 300 membrane installation instructions, including information on substrate preparation and membrane installation, can be found on **traxxcorp.com**.

Approved Floor Coverings

The following products have been approved for use with the KOVARA® / VAPORSHIELD™ AB 300 floor moisture barrier, when installed according to the manufacturers' recommendations.

- Carpet tile
- · Vinyl composition tile (VCT)
- Solid vinyl tile (SVT)
- Luxury vinyl tile/luxury vinyl plank (LVT/LVP)
- Static dissipative tile (SDT)
- Laminate flooring
- Ceramic tile
- Porcelain tile
- Natural stone
- Broadloom carpet
- Woven synthetic-backed stretch-in, double glue and direct glue carpet
- PVC-backed carpet
- Urethane foam-backed carpet
- Compressed urethane-backed carpet
- Recycled-backed carpet
- · Engineered wood-floating or direct glue
- Bamboo flooring

The KOVARA® system can also be used on specialty floors such as:

- Commercial and residential sheet vinyl flooring
- Rubber flooring
- · Resilient sports flooring
- Wood court flooring

traxxcorp.com | Customer Service: 1-909-623-8032

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

TRAXX Corporation, TRAXX, VERSASHIELD and KOVARA are trademarks, which may be registered in the United States and/or other countries, of TRAXX Corporation. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

 $\ \, \mathbb{O}$ Copyright 2023 TRAXX Corporation. All rights reserved.

HEADQUARTERS: 1201 E. Lexington Avenue · Pomona, CA 91766 | USA.

KOV-TRAXX-0223 · KOVARA AB 300 Sell Sheet