

DUO-FAST®

JET-TAC™

A single 10oz cartridge covers 90-150 linear feet!

FOR WOOD AND CONCRETE FLOORING APPLICATIONS *Ideal for:*

- **Tack Strip Installation**
- **Transitions**
- **Carpet Repairs**
- **Cove Mouldings**
- **Carpet Shims**
- **Metals**
- **Stone**
- **Ceramic**
- **Glass**



3-Pack of Nozzles
DFG-6565-3N



10 oz (250ml) + Applicator Nozzle
DFG-6565

FEATURES:

- **2-Part Epoxy***
- **Static Mixing Nozzle**
- **Fits Standard Size Caulking Gun** (recommend 12:1 or greater thrust ratio)
- **Sets-up in 5–7 minutes**
- **2-Hour Cure Time**

*Two-part epoxy consists of a **clear** component and a **blue** component to help ensure an equal blend.

BENEFITS:

- **Versatile** — *use on Multiple Surfaces / Applications*
- **Superior Holding Power** — *Power Stretch*
- **Easy-to-Use / No Mess**

Rev. 1/2025

DISTRIBUTED EXCLUSIVELY BY TRAXX

1201 E. Lexington Avenue | Pomona, CA 91766 | 909-623-8032
www.traxxcorp.com

TRAXX
CORPORATION